



Specifications Ledvance LED  
Floodlight Max Radial 45 Aluminium  
Grey 600W 76400lm 45D - 830 Warm  
White | IP66 - Symmetrical

[View Product](#)

General Information

|                          |                                                     |
|--------------------------|-----------------------------------------------------|
| SKU                      | 260333                                              |
| EAN                      | 4099854682353                                       |
| Manufacturer Code        | 4099854682353                                       |
| Brand                    | Ledvance                                            |
| Manufacturer Name        | FLOODLIGHT MAX RADIAL SYMMETRIC 45 600W 857 R45 WAL |
| Any Lamp all-in warranty | 5 Years                                             |
| Average Lifetime (h)     | 115000                                              |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 600W            |
| Replaces (Watt)             | 600             |
| Voltage (V)                 | 330             |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 857 Cool White  |
| Colour temperature (Kelvin) | 5700 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 76400lm         |

|                          |                |
|--------------------------|----------------|
| Luminous Efficacy (lm/W) | 127            |
| Beam Angle (degree)      | 45             |
| Tiltable                 | No             |
| Power factor             | >0.93          |
| Product Type Category    | LED Floodlight |

## Fixture Information

|                        |                       |
|------------------------|-----------------------|
| Mounting Method        | Ceiling, Wall mounted |
| Optical Cover          | Clear                 |
| Light Distribution     | Symmetrical           |
| IP-rating              | IP66                  |
| Impact Protection (IK) | IK08 - 5 joules       |
| Colour of the Fixture  | Grey                  |
| Housing                | Aluminium             |
| Emergency Lighting     | No Emergency Unit     |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 589 |
| Width (mm)  | 250 |
| Height (mm) | 95  |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process